

ACTIVBOARD+2 FIXED

PROVISIONAL ACTIVBOARD+2 FIXED PRODUCT SPECIFICATIONS

Activboard general specification:

Tracking rate	200 inches per second
Output rate	120 coordinate pairs per second
Pointing device	Cordless Battery-free pen incorporating tip switch and side switch for full mouse functionality.
Digitising technology	Passive Electromagnetic
Built In functionality	Radio Frequency (EU 868Mhz, US 915Mhz) as standard for Activote and Activslate.
Interface	RS232 to host at up to 38.4kbs. or USB 1.1/2
Screen surface	Low Glare Melamine
Power requirements	6 Volt 0.5 Amp
	Pack Contents Activboard, 2 x Pens, Activ Software and resource CD, PSU & power cord, USB cable, DC power lead (to connect PSU to board), Mounting brackets and template, Safety guidelines, Quickstart guide

Activboard 78 Specification:

Resolution	12800 x 9600
Overall dimensions	1693 x 1239mm (67 x 49")
Active area dimensions	1624 x 1160mm (64 x 46")
Active area diagonal	1995mm (78")
Board weight	17kg (37lb)
Packed weight	28kg (62lb)
Packed Dimensions	184 x 140 x 10.5cm (72.4 x 55 x 4")

Activboard 64 Specification:

Resolution	10000 x 8000
Overall dimensions	1351 x 1076mm (53 x 42")
Active area dimensions	1280 x 1005mm (50 x 40")
Active area diagonal	1627mm (64")
Board weight	13kg (29lb)
Packed weight	24kg (53lb)
Dimensions:	149 x 122 x 10cm (58 x 48 x 4")

Activboard warranty information

Activboard	Three year limited equipment warranty
------------	---------------------------------------

ACTIVBOARD+2 FIXED

PROVISIONAL ACTIVBOARD+2 FIXED PRODUCT SPECIFICATIONS

Fixed frame specification:

Board Size:	Accommodates either 64" and 78" Activboard.
Projector mount:	Aluminium arm, extends 1270mm (50") from the board.
Power:	Integrated 'power management' system for Activ board, Projector and Speaker system (where supplied).
Weight (approx.):	Frame only: 30kg (66lbs) excl. board, projector and audio speakers and cabling.
Complete system weight:	TBC
Cable kit contents:	Connectivity box with inputs for 2 x PC inputs (VGA & Audio RCA), S-video and composite video, plus Auxiliary audio RCA inputs. Box also has VGA switch for PC inputs and volume control for audio output cable. Box is mounted to the wall and can be placed on either side of the system. 2m (6 ft). USB patch cable (to connect computer to face plate) 2m (6 ft). 3.5mm Jack to RCA cable for PC audio input (to connect computer to face plate). 6 ft. VGA cable (provided in the projector box) to connect the computer to the face plate.
Pack weights and dimensions:	Box 1 of 2: 20kg Dimensions: 1400x300x150mm Contents: TBC Box 2 of 2: 20kg Dimensions: 865x380x220mm Contents: TBC

Fixed frame warranty information:

Frame & cables:	TBC
-----------------	-----

ACTIVBOARD+2 FIXED

PROVISIONAL ACTIVBOARD+2 FIXED PRODUCT SPECIFICATIONS

Projector Specification:

Brand/model:	Promethean PRM-10
Screen size/Throw distance:	60" ~ 80" 72.7 ~ 98.1 cm via fixed super short focus lens
Display type:	True XGA (1024 * 768)
Display technology:	LCD, 0.63" TFT p-Si x 3 with Micro Lens
Brightness:	1500 ANSI lumens in Normal mode 2000 ANSI lumens high mode
Lamp life expectation:	3000 hrs (normal mode), 1500 hrs (high mode)
Aspect ratio:	4:3 native (with support for 16:9)
Contrast ratio:	450:1
Color systems:	NTSC / NTSC4.43 / PAL / SECAM / PAL-M/N
HDTV compatibility:	480i, 480p, 575i, 575p, 720p, 1035i and 1080i
Computer compatibility:	UXGA / WXGA / SXGA / XGA / SVGA / VGA and MAC
Scanning rate:	H/V sync approx. 100kHz, 100Hz
Connectors:	2 x Composite D-SUB15, first for PC input, 2nd for PC input or monitor output (selectable) RCA for Composite video input Mini-DIN 4-pin for S-video input RCA audio input pair Mini-jack (stereo) for PC input Mini-jack (stereo) for audio output (variable) RS232C service and Control Mini DIN 8-pin USB type B AC power inlet
Projector noise:	31dBA (normal), 38dBA (High)
Power consumption:	230W normal, 275W High, 9W standby
Security features:	Remote-only operation, pin-code lock, sonic alarm (100dB), user logo feature (with lock)
Dimensions:	320x148x292mm (12.6x5.8x11.5"), not including protrusions.
Weight:	3.3kg (7.3lb)
Input voltage:	100V – 240V AC (auto voltage)
Lamp management:	'Lamp save' feature to reduce risk of lamp failing in the event of interrupted power supply.
Packed Weight:	6.3kg (13.9lb)
Packed Dimensions:	29x43x43cm (11x17x17")
Pack contents:	Projector, 2m (6ft) mains cord, 2m (6ft) VGA cable, Remote control and batteries, User guide (Paper and CD).

Projector warranty information:

PRM-10 projector:	Three year swap out limited equipment warranty;
90 day warranty on lamp	

ACTIVBOARD+2 FIXED

PROVISIONAL ACTIVBOARD+2 FIXED PRODUCT SPECIFICATIONS

Powered speaker specifications:

Woofers:	5" Polypropylene
Tweeters:	1" Dome
Power:	15W (RMS) per channel
Frequency response:	60Hz~18KHz
Sensitivity:	89 dB
Voltage & frequency	115V @ 60Hz/230v @ 50Hz (switchable)
Equalization:	2 bands EQ ± 15 dB
Gain:	30dB(max)
Dimension (HxWxD):	240x178x145mm
Net weight (1pair):	5.6kgs (12lb)
Packed weight and dimensions:	Packed with Fixed frame system.

Speaker warranty

Speakers: One year limited equipment warranty

